

Datacard® CP80™ Plus Card Printer



The CP80 Plus card printer enables government agencies, corporations, universities and others to produce the most technologically advanced secure IDs available anywhere.

Superior security and durability

The Datacard® CP80™ Plus card printer can support even the most demanding ID programs. It produces high-quality secure ID cards that help you protect people, facilities and other critical assets. This printer can personalize contact or contactless smart cards, encode magnetic stripe cards and issue proximity cards. It is also optimized to work with Datacard® IDCentre™ identification software and capture solutions, as part of a fully integrated system.

Enhance security and durability

- One standard laminator and a second optional laminator can both apply Datacard® DuraGard® virtual edge-to-edge laminates, which cover 95% of the card to increase security and durability.
- Laminate any combination of topcoats or DuraGard laminates in a single pass. Apply different laminates to each side to improve cost-efficiency.
- Ultraviolet (UV) fluorescent printing comes standard for enhanced security.
- Security features include theft-deterrent software and a hardware lock system.



Datacard® CP80™ Plus Card Printer

100- or 200-card input hopper

Quick-change supplies switch out in seconds

Standard LCD panel offers at-a-glance print status

One (standard) or two (optional) laminators

Optional theft-deterrent software and hardware lock system

Front-facing output hopper saves space

Standard Ethernet and USB connectivity



Configure your CP80 Plus card printer with one or two laminators for applying DuraGard virtual edge-to-edge laminates or topcoats.

Standard features

- One- or two-sided edge-to-edge printing
- Continuous-tone for full-color or black-and-white photos
- Ultraviolet fluorescent printing
- Alphanumeric text, logos and digitized signatures
- Variety of bar codes and background patterns
- Automatic printer settings and offsets, automatic ribbon identification, validation and low ribbon warning
- Full-color print speed of up to 175 cards per hour (one-sided), up to 165 cards per hour (two-sided) and up to 105 cards per hour (two-sided, print and laminate)
- Choose topcoat or patch lamination with superior coverage or lamination without printing
- Bi-directional USB supported on Microsoft® Windows® 2000, XP and Windows Vista® operating systems
- Ethernet 10/100 Base-T bi-directional networking supported on Windows 2000, XP and Windows Vista operating systems
- Printer driver pooling supported on Windows 2000, XP and Windows Vista operating systems
- Datacard® Open Platform printer driver for non-Windows platforms
- Printer driver features user-adjustable image and color controls, stand-alone driver diagnostics, color image and text card preview, online user help, add text, pattern or image to topcoat, and supply usage tab
- Backlit LCD panel
- Audible and visual message prompts on printer and PC
- Automatic card feed
- Quick-change ribbon and laminate cartridges
- 24-month standard depot printer and printhead warranty

Options

- Second laminator
- ISO magnetic stripe encoding (IAT; dual high-and low-coercivity; tracks 1, 2 and 3 for IAT)
- Smart card options include contact and contactless all-in-one readers; contact station; Prox by HID; and iCLASS® by HID
- 100- or 200-card input hopper
- 100-card output hopper
- Magnetic stripe and smart card field upgradeability
- Input hopper empty alert
- Printer-PC security software
- Hardware lock system

Specifications

Dimensions: L 23.1 in. x W 9.92 in. x H 18.82 in. to H 23.52 in. (58.76 cm x 25.2 cm x 47.8 cm to 59.74 cm)

Weight: Less than 27 lbs. (12.25 kg) without supplies

Print resolution of 300 dots per inch, 256 shades

Electrical requirements of 100/120V, 50/60 Hz; or 220/240V, 50/60 Hz

Accepts ID-1/CR-80 size cards measuring 3.370 in. x 2.125 in. (85.6 mm x 53.98 mm); accepts glossy-surfaced PVC cards; other core materials with PVC overlaminates are optional

Accepts card thickness from 0.02 to 0.05 in. (0.51mm to 1.27mm) + 10%, for print-only; 0.03 to 0.05 in. (0.76mm to 1.27mm) + 10% for print and laminate

Operates in temperatures from 60° to 95°F (15° to 35°C) and non-condensing humidity from 20% to 80%

Agency approvals: UL (safety); FCC CFR47, Part 15, subparts b and c, class A (FCC Emissions); RoHS (EU and China)

Datacard® Certified Supplies featuring Intelligent Supplies Technology™

Datacard Group sales channels are your exclusive source for Datacard® Certified Supplies. Datacard® CP Series card printers require the use of Datacard Certified Supplies in order to print and laminate properly.

DatacardGroup

11111 Bren Road West
Minnetonka, MN 55343-9015
+1 952 933 1223
www.datacard.com