

TRANSFORM SECURE IDENTIFICATION

As part of an integrated solution, the SP75 Plus card printer is ideal for enhancing the security and durability of government and other secure IDs. Rely on the SP75 Plus card printer for fast issuance of:

- Contactless smart cards
- · Contact smart cards
- Proximity cards including HID® iCLASS® smart cards for access control
- Conventional ID cards with ISO magnetic stripes and bar codes
- Corporate IDs
- Student, faculty and staff IDs
- Police or emergency services IDs
- National IDs
- Drivers Licenses
- Vehicle Registration IDs
- Ministry of Defense IDs

Protect your enterprise with advanced security technologies

Engineered to produce highly secure IDs, the Datacard® SP75 Plus card printer enables government agencies, high-tech corporations, universities and other security-minded organizations to protect people, facilities and critical assets.


- Intense security. The SP75 Plus card printer offers one standard laminator and a second optional laminator, both of which can apply Datacard® DuraGard® virtual edge-to-edge laminates that cover 95% of the card. These laminates extend card life and help defend against tampering. Ultraviolet fluorescent printing capability comes standard. Additional security features include theft deterrent software, a hardware lock suite that secures active supplies, blank card stock and rejected cards, and a Kensington® lock that secures the printer itself.
- High durability. The SP75 Plus card printer delivers the consistency and reliability
 that colleges, universities and others need to maximize card quality and efficiency.
 With fewer moving parts and a significantly higher duty cycle, the SP75 printer offers
 exceptional reliability for the most demanding applications.
- Diverse functionality. Use the SP75 Plus card printer to laminate cards printed by another printer or print cards without laminating. You can apply the same security laminate to both sides of the card or apply different laminates to each side to improve cost-efficiency. The printer also offers field upgradable options for smart card, proximity card and magnetic stripe encoding.



DATACARD® SP75 PLUS CARD PRINTER

Blank card stock secured in a 100- or 200-card input hopper

Backlit LCD offers at-a-glance print status





Lock suite secures cards, ribbons and laminates



Secure storage for rejected cards



Choose one or two laminators with quick-change cartridges



Ethernet port for network connectivity



Configure your SP75 Plus card printer with one or two laminators for applying DuraGard virtual edge-to-edge laminates or topcoats.

Standard Features

Print capabilities

One- or two-sided edge-to-edge printing

Full-color or monochrome

Ultraviolet fluorescent printing

Continuous-tone, full-color, black-and-white photos

Alphanumeric text, logos and digitized signatures

Variety of bar codes

Background patterns

Printer pooling

Advanced Imaging Technology™

Full-color print speed

Up to 175 cards per hour (one-sided print and laminate)

Up to 165 cards per hour

(two-sided print and laminate)

Up to 105 card per hour

(two-sided print and two-sided laminate)

Printer Memory

32MB Standard

Lamination and topcoat capabilities

Topcoat or patch lamination

Superior laminate patch coverage

Laminate without printing

Connectivity

Bi-directional USB and Ethernet

10/100 Base-T bi-directional networking

Input hopper: 100 cards, 0.03 in. (0.76mm)

Output hopper: 40 cards, 0.03 in. (0.76mm)

Printer driver

User-adjustable image and color controls

Stand-alone driver diagnostics

Color image and test card preview

Online user help

Add text, pattern or image to topcoat

Supply usage tab

User-friendly operation

Backlit LCD panel

Audible and visual message prompts

Automatic card feed

Quick-change ribbon and laminate cartridges

Datacard® Certified Supplies featuring

Intelligent Supplies Technology"

Automatic identification and validation for ribbons,

laminates and topcoats

Automatic printer settings and offsets

Ribbon low warning

Ribbon saver

Warranties

24-month standard depot warranty

24-month printhead warranty (no pass restrictions)

Options

Second laminator

Magnetic stripe encoding

ISO: IAT or NTT

Dual high and low coercivity

Tracks 1, 2 and 3 (1 track for NTT)

Smart card personalization

Contact/contactless all-in-one reader

Contact PC USB Reader

Contact station

Prox by HID

iClass® by HID

Magnetic stripe and smart card field upgradeability

Input hopper empty detection

Printer-PC security software

Hardware lock suite

200-card input hopper

100-card output hopper

Customized service plans

Specifications

Physical dimensions

L 23.1 in. x W 9.92 in. x H 18.82 in. to 23.52 in. (58.76 cm x 25.2 cm x 47.8 cm to 59.74 cm)

Weight

Less than 27 lbs. (12.25 kg) without supplies Print resolution

300 dots per inch, 256 shades

Electrical requirements

Dual voltage auto-sensing

100/120V, 50/60 Hz

220/240V, 50/60 Hz

Plastic cards accepted

ISO ID-1/CR-80 size cards

3.370 in. x 2.125 in. (85.6mm x 53.98mm)

PVC with glossy laminate surface

Other core materials with PVC overlaminates are optional

Card thickness accepted (±10%)

Print only: 0.02 to 0.05 in. (0.51mm to 1.27mm)

Print and laminate: 0.03 to 0.05 in.

(0.76mm to 1.27mm)

Operating environment

60°F to 95°F (15°C to 35°C)

20% to 80% non-condensing humidity

Storage conditions

5°F to 140°F (-15°C to 60°C)

10% to 90% humidity

Operating system support

Microsoft® 7, Windows Vista®,

Windows® XP,

Windows® 2003 Server, and

Windows® 2008 Server supported on printer driver

version 4.0

Windows® 2000 supported by printer driver version 2.0

Datacard® Open Platform printer driver for non-

Agency approvals

Windows platforms

UL, cUL, FCC, CE, CCC, Ctick, RoHS

Datacard Group

CORPORATE HEADQUARTERS

11111 Bren Road West Minnetonka, Minnesota 55343-9015 www.datacard.com

Datacard, DuraGard, Intelligent Supplies Technology and Advanced Imaging Technology are trademarks, registered trademarks, or service marks of DataCard Corporation in the United States Datasata, Butasata, Intergrat Spirity Rectaining and Architecture magnifer technology are trademarks, regreted trademarks, in an analysis of the countries. Microsoft, Windows and Windows Vista are registered trademarks of Microsoft Orporation. Rensington is a registered trademark of ACCO World Corporation. iClass is a registered trademark of HID Corporation. Names and logos on sample cards are fictitious. Any similarity to actual names, trademarks or trademark