

Datacard® 295 Card Personalization System



The Datacard 295 system gives healthcare providers a fast, secure way to issue attractive patient IDs and other personalized cards that build your brand, improve the patient experience and help reduce costs.

Produce high-impact patient IDs quickly

In a fast, single-pass operation, the Datacard® 295 card personalization system enables healthcare providers to issue high-quality patient ID cards imprinted with a choice of embossed characters, bar codes, logos, text, graphics, encoded magnetic stripes and smart card chips. Rely on this convenient system for the capabilities you need to implement a powerful patient ID program that helps increase patient loyalty and decrease costs.

Improve customer service and build loyalty

- Strengthen your image as a high-quality provider by adding graphics and logos to cards.
- Use magnetic stripe encoding, bar code printing and smart card personalization technologies to store patient data and accelerate customer service.
- Minimize capital investment with the system's modular design. Start with embossing, adding other capabilities as you need them.
- Save time and money with robust software that lets you convert existing data to graphics or encoding without modifying your hospital information system.

Datacard® 295 Card Personalization System



The Datacard® 295 card personalization system issues patient IDs and other high-quality healthcare cards instantly.

Standard features

93-character embossing wheel
Dual operating mode (online or offline)
Error recovery software
Automatic card counter
RS-232 communications
2-line by 40-character message display
Nine stored formats
Password access
Field-upgradeable
Security keylock on system cabinet
Print drivers for Microsoft® Windows® 95, 98, 2000 Professional, XP and Windows NT® 4.0 operating systems

Options

327X or 5256 internal communication interface
Printer interface
Pop-up keyboard
Detached typewriter-style keyboard
CRT/keyboard
Aluminum card embossing
CR-80 or CR-50 card capability
Automatic card feed
200-card input hopper
Security keylock on input hopper
Variety of card output configurations
Datacard® UltraGrafix® printing
Magnetic stripe encoding
Color topping
Smart card personalization
Data conversion utility software

Datacard® ID Works® identification software (Microsoft® Windows® 2000 Professional or XP operating systems)
User prompts in language of choice

Specifications

Dimensions (with output hopper): L 25.0 in. x W 17.75 in. x H 16.5 in. (635 mm x 451 mm x 412 mm)
Footprint: 15.0 in. x 14.74 in. (381 mm x 375 mm), 19.75 in. x 15.5 in. (502 mm x 394 mm) with color topping module, 21.25 in. x 14.75 in. (540 mm x 375 mm) with extended cabinet
Weight: 80 lbs. (36.3 kg), 123.0 lbs. (55.8 kg) with topper, 111.0 lbs. (50.4 kg) with extended cabinet
Embossing speed of up to 380 cards per hour
Electrical requirements of 120V, 50/60 Hz or 240V, 50/60 Hz
Accepts CR-80 cards from 0.020 in. to 0.030 in. thick (0.51 mm to 0.76 mm) and CR-50 cards from 0.020 in. to 0.030 in. thick (0.51 mm to 0.76 mm)
Agency approvals: UL, CE, TUV GS, FCC, CSA

DatacardGroup

1111 Bren Road West
Minnetonka, MN 55343-9015
+1 952 933 1223
www.datacard.com